

PA-LHC33.R001



Dimensions

Length	67mm	±1mm
Width	18.6mm	±0.5mm
Height	59mm	±1mm

Data for Pack

Nominal voltage		3.6V	2.5V - 4.2V
Nominal capacity		8700mAh	typical (8100mAh rated)
Used cell in pack		3pcs	Panasonic NCR-18650PF
Internal resistance pack		44.5mΩ	±10%
Charge voltage		4.2V	max.
Charge current	max	4.125A	10°C < T < 45°C
	standard	5A	-20°C < T < 60°C *1)
Discharge	max. cont.	10A	0°C < T < 40°C
	max. peak	20A	0°C < T < 40°C t < 5ms
	NTC	10kΩ	Tolerance ±3%; B-value 25°C/85°C = 3980K
Connector	Molex	UltraFit	Pin1 VBAT+ Red
			Pin2 NTC Yellow
			Pin3 GND Black
Cable Length		90mm	±10mm
Weight		ca. 148g	±5g
Watt-hour rating		29.4Wh	acc. to UN38.3 Certificate

*1) discharge in ambient temperatures lower than 0°C will result in limited performance in current output and usable capacity

Limitations by Safety Unit (SU) @ Ta 25°C

Over voltage (per cell)	cut off	4.275V	±0.025V
	release	4.075V	±0.025V
Under voltage (per cell)	cut off	2.3V	±0.05V
	release	2.3V	±0.05V
Current Limit by SU		17A	>9ms (±2A)
Short circuit protection		Yes	Implemented in Safety Unit
Current Fuse		20A	non reversible
Power consumption	active	20μA	max 35μA
	power down	2μA	max 5μA (power down when Ubat < 2.3V)

Recommended Charger

C-LIO-1SN15-1,8M-DIN4--PNG.R001