

PA-UL-ICR33E.R001



Dimensions

Length	67	± 1mm
Width	22.5	± 0.5mm
Height	55	± 1mm



MH45979



IEC 62133 2nd. Ed.

Data for Pack

Nominal voltage	3.6V	2.75V - 4.2V		
Nominal capacity	6600mAh	typical		
Used cell in pack	3pcs	Samsung ICR-18650-22F		
Internal resistance pack	48mΩ	±10%		
Charge voltage	4.2V	max		
Charge current	standard	1.1A		
	rapid	3A		
Discharge	standard	0.44A		
	max. cont.	3A		
	max. peak	5A		
Short circuit current	≤ 89A	< 380μs		
NTC	10kΩ	Tolerance ±3%; B-value 25°C/85°C = 3980K		
Connector	JST	XHP-3	Pin1	GND
			Pin2	NTC
			Pin3	Bat+
Cable Length	45mm	± 5mm		
Weight	ca. 132g	± 5g		
Watt-hour rating	23.76Wh	acc. to UN38.3 Certificate		

*1) discharge in ambient temperatures lower than 0°C will result in limited performance in current output and usable capacity

Limitations by Safety Unit (SU) @ Ta 25°C

over voltage (per cell)	cut off	4215mV	± 25mV
	release	4100mV	± 25V
under voltage (per cell)	cut off	2300mV	±50mV
	release	2400mV	±50mV
Current Limit 1 by SU		≤ 4A	continous typical
Current Limit 2 by SU		≥17.9A	2.24ms (typical)
short circuit protection		≥42.9A	380μs (typical) ±10A
Power consumption	active	15μA	±5μA
	power down	8μA	±2μA

Recommended Charger

C-LIO-1SN15-1,8M-DIN4-GPN-.R001